

StoSuperlit®

Organic natural stone render
Collection K 0.8



Area of application

- Exterior
- On rendered masonry
- On insulated facades
- On mineral base coats with undercoat
- Particularly suitable for impact-loaded plinth areas and passageways
- Not suitable for horizontal or sloping surfaces that are exposed to weather conditions
- For application in the facade area always with field-delimiting joint pattern

Properties

- Mixed aggregate render with transparent binder
- Tinted quartz sand and mica
- With heat-reflective X-black Technology
- Highly weather-resistant
- Water vapour permeable
- Without biocide film protection



Note

Always apply StoSuperlit K with an undercoat in a complimentary colour.



Appearance

Collection of 8 colour shades StoSuperlit K 0.8

Colour shade

Colour shades collection K 0.8: no special colour shades possible




Collection


Approx. consumption

2.00–2.50 kg/m² per layer


Application




08-800 (00152-141)
TSR: 13 LRV: 4



08-810 (00152-142)
TSR: 19 LRV: 8



08-820 (00152-143)
TSR: 17 LRV: 10



08-830 (00152-144)
TSR: 16 LRV: 6



08-840 (00152-145)
TSR: 30 LRV: 20



08-890 (00152-150)
TSR: 30 LRV: 26



08-900 (00152-151)
TSR: 42 LRV: 39



08-910 (00152-152)
TSR: 51 LRV: 51

Headquarters | Market Development

Sto SE & Co. KGaA
Ehrenbachstrasse 1
79780 Stühlingen

Info service

Phone +49 7744 57-1131
info.international@sto.com
www.sto.com

